UC-SILENTIS

NEW

Energy-efficient.
Minimal and low-noise.

- **Simple and compact installation with Curved Frontal Design.**
- High Performance plastic Housing design and Helico-Centrifugal Impeller.
- **Very Low Noise Level**
- Fitted with Low Consumption Motor class B and thermal cut out, ambient temperature max. 40ºC
- Rated Voltage 220-240V 50/60Hz.
- Timer and Timer-Hygro models available
- IP-44 and Double Insulation
- Basic Back draught Shutter (included)







Coming soon.

CODE	MODEL	COLOR	EAN CODE	VERSION	Ø (mm)	Voltage (V)	SPEED (r.p.m)	Imput Power (W)	Maximum Airflow (m^3/h)	Sound Pressure Level dB(A)	Weight (Kg)	Units per box	110-127V 60Hz on request
HYGRO SERIES													
01220200	**UC-10 SILENTIS HYGRO WHITE**	☐	8422248365451	●●	100	230	2300	8	105	26	0,60	6	-
01221200	**UC-10 SILENTIS HYGRO SILVER**	▪	8422248365475	●●	100	230	2300	8	105	26	0,60	6	-
01222200	**UC-10 SILENTIS HYGRO BLACK**	■	8422248365468	●●	100	230	2300	8	105	26	0,60	6	-
TIMER SERIES													
01220100	**UC-10 SILENTIS TIMER WHITE**	☐	8422248365420	●	100	230	2300	8	105	26	0,60	6	-
01221100	**UC-10 SILENTIS TIMER SILVER**	▪	8422248365444	●	100	230	2300	8	105	26	0,60	6	-
01222100	**UC-10 SILENTIS TIMER BLACK**	■	8422248365437	●	100	230	2300	8	105	26	0,60	6	-
STANDARD SERIES													
01220000	**UC-10 SILENTIS STD WHITE**	☐	8422248365390	●	100	230	2300	8	105	26	0,60	6	√
01221000	**UC-10 SILENTIS STD SILVER**	▪	8422248365413	●	100	230	2300	8	105	26	0,60	6	√
01222000	**UC-10 SILENTIS STD BLACK**	■	8422248365406	●	100	230	2300	8	105	26	0,60	6	√

STANDARD In combination with light, fans switches on.

TIMER Electronic timer adjustable from 3 to 15 minutes.

HYGRO Adjustable humidity detector from 40% to 95%, and adjustable electronic timer from 0 to 15 minutes.

UC-SILENTIS

